

**WOOD PANEL WINDOW PROTECTION AFFIDAVIT  
For Construction Within One (1) Mile Of The Ocean**

This affidavit is submitted for the purpose of confirming compliance to the Exception of section 5301.2.1.2 Internal Pressure.

**5301.2.1.2 Internal Pressure.** Windows in buildings located in wind borne debris regions shall have glazed openings protected from windborne debris or the building shall be designed as a partially enclosed building in accordance with the *International Building Code but utilizing the wind loads set forth in 780 CMR 51.00 through 99.00*. Glazed opening protection for windborne debris shall meet the requirements of the Large Missile Test of ASTM E 1996 and of ASTM E 1886 referenced therein.

**Exception:** Wood structural panels with a minimum thickness of 7/16 inch (11.1 mm) and a maximum span of eight feet (2438 mm) shall be permitted for opening protection in one-and two-story buildings. Panels shall be precut to cover the glazed openings with attachment hardware provided. Attachments shall be provided in accordance with 780 CMR Table 5301.2.1.2 or shall be designed to resist the components and cladding loads determined in accordance with the provisions of the *International Building Code but utilizing the wind loads set forth in 780 CMR 53.00.*

Also supplied Fasteners in accordance to section:

780 CMR TABLE 5301.2.1.2  
WINDBORNE DEBRIS PROTECTION  
FASTENING SCHEDULE FOR WOOD  
STRUCTURAL PANELS

I as the Contractor/Provider of the required panels and attachments that have been placed at an approved location within the building located at:

Address: \_\_\_\_\_

Application #: \_\_\_\_\_

Contractor/Provider: \_\_\_\_\_ Print Name: \_\_\_\_\_